



SS-FUSION-TT

Time and Temperature Large Digit Display

KEY FEATURES

- 4 or 6 digits
- 5 digit colours available
- Indoor or outdoor brightness
- IP66 sealed
- 316L stainless-steel enclosure
- Real Time Clock module, temperature sensor
- Viewing distances up to 110m
- AC or DC powered
- Wall or suspension mounting
- Alarm, analogue and data output options


DESCRIPTION

SS-FUSION large digit displays are primarily used for displaying numerical information which is visible from a distance. In addition, the displays have several analogue, alarm and data output options which can work with systems already in situ to control processes within the system.

The SS-FUSION-TT is available as 4 or 6 digits and uses a Real Time Clock module and internal sensor to show the time and temperature.

DIMENSIONAL DRAWINGS

Wall or Suspension Mounting



DIMENSIONS (mm)

Model	Digit Format	Width (A)	Height (B)	Depth (C)
SS-F2-4N	2" 4 digit	350	225	100
SS-F2-6N	2" 6 digit	450	225	100
SS-F4-4N	4" 4 digit	525	250	100
SS-F4-6N	4" 6 digit	700	250	100
SS-F6-4N	6" 4 digit	625	350	100
SS-F6-6N	6" 6 digit	850	350	100
SS-F8-4N	8" 4 digit	800	400	100
SS-F8-6N	8" 6 digit	1125	400	100

Notes:

- i. E & OE

TECHNICAL DATA

Digit Height (inches)	2.2 (SS-F2)	4.0 (SS-F4)	5.9 (SS-F6)	7.9 (SS-F8)
Digit Height (millimeters)	57	102	150	200
Viewing Distance (feet)	82	180	262	360
Viewing Distance (metres)	25	55	80	110
Number of Digits	4 or 6			
Digit Format	8.8.8.8. or 8.8.8.8.8.8.			
Accuracy	Better than +/- 10 seconds per month			
Battery Backup	CR1620 3V Lithium (retains time in memory during power loss but display is not lit)			
Input Signal	3-wire PT100 DIN, ANSI, Thermocouple type J,K,N,R,S,T, Real time clock module (DS3231SN)			
Excitation Voltage	24V @ 30mA			
Digit Colour	Green, red or yellow. Blue and white available for 6" and 8"			
Brightness	Indoor or outdoor with 7 levels of adjustment			
Power Supply	95-265V AC (standard), 11-30V DC (optional), 48V AC (optional)			
Power Burden	40VA maximum			
Mounting	Brackets supplied for wall or suspension mounting			
Logic Inputs	3 x NPN or contact closure for TARE, PEAK/VALLEY and RESET			
Environmental				
Enclosure Material	316L stainless-steel			
Lens Material	Polycarbonate, 6mm			
Sealing	IP66			
Storage Temperature	-20°C to +70°C, non-condensing			
Operating Temperature	0°C to +50°C, non-condensing			
Connectors	Internal detachable screw terminal connectors accessed via compression glands			
Analogue Output (optional)				
ANB Option	-10 to +10V into loads >1k Ohms, resolution 0.4mV			
ANI Option	0-20mA or 4-20mA into loads <500 Ohms, resolution 0.4uA			
ANV Option	0-10V into loads >1k Ohms, resolution 0.2mV			
Scaling	Fully adjustable, direct or inverse. Can be derived from GROSS or NETT value			
Response Speed	Derived from displayed value, updated x10 per second, display filtering applies to analogue output			
Linearisation	Derived from displayed value			
Isolation	250V AC optically isolated from input, logic, excitation, power, alarms and data output ports			
Accuracy	+/- 0.1% of range			
Linearity	+/- 0.02% of range			
Stability	+/- 50ppm/°C			
Alarm Outputs (optional)				
AL2 and AL4 Option	2 or 4 x SPST mechanical relays, 2A @ 250V AC, resistive load			
DSS and QSS Option	2 or 4 x solid state relays, specify AC or DC, 100mA max @ 250V AC, 500mA max @ 60V DC			
SPCO Option	2 x SPCO mechanical relays, 2A @ 250V AC, resistive load			
Response Speed	For mechanical relays allow 105mS, for solid state relays allow 100mS			
Data Output (optional)				
232 Option	RS232 ASCII			
485 Option	RS422/RS485 ASCII + Modbus ASCII			
RTU Option	Modbus RTU			
Response Speed	Derived from displayed value, updated x10 per second, display filtering applies to data output			
Isolation	250V AC optically isolated from input, logic, excitation, power, alarms and analogue output ports			

ORDERING GUIDE

Digit Height:		SS-X	-X	-TT	-X	-X	-X	-X	-X	-X
F2 2 inches (57mm)	F4 4 inches (102mm)									
F6 6 inches (150mm)	F8 8 inches (200mm)									
Digit Format:										
4N 8.8.8.8. - 4 digit, numeric format										
6N 8.8.8.8.8.8 - 6 digit, numeric format										
Function / Input Type:										
T Time and Temperature										
Analogue Output:										
0 None	ANB -10 to +10V	ANI 4-20mA	ANV 0-10V							
Alarm Outputs:										
0 None	AL2 2 x SPST mechanical relays	AL4 4 x SPST mechanical relays								
DSS 2 x solid state relays (specify AC or DC)	QSS 4 x solid state relays (specify AC or DC)									
SPCO 2 x SPCO mechanical relays										
Data Output:										
0 None	232 RS232	485 RS422/485 + Modbus ASCII	RTU Modbus RTU							
Digit Colour:										
Indoor		Outdoor								
B Blue 6" and 8"	G Green	BDLV Blue 6" and 8"	GDLV Green							
R Red	W White 6" and 8"	RDLV Red	WDLV White 6" and 8"							
Y Yellow		YDLV Yellow								
Power:										
48VAC 48V AC	AC 95-265V AC	DC 11-30V DC								
Mounting:										
2	Wall, cable glands on bottom surface									
3	Suspension, cable glands on bottom surface									
4	Wall, cable glands on top surface									
5	Suspension, cable glands on top surface									

